

Part Number: AE-SB16005PH

10/100 SMD LAN Transformer

Page: 1/2

- Compliant with IEEE 802.3at standard.
- Power over Ethernet (PoE) Magnetics, 720mA current capability.
- RoHS compliant.
- Operating temperature range: -40°C to +85°C.
- Storage temperature range: -40°C to +125°C



Electrical Specifications



Part Number	Turns Ratio (±5%)		OCL(μH Min) @100KHz/0.1V with 8.0mA DC	Insertion Loss (dB Max)	HI-POT (Vrms)
	TX	RX		1-100MHz	
AE-SB16005PH	1CT:1CT	1CT:1CT	350	-1.0	1500

Continue



Part Number	Return Loss (dB Min)				Cross Talk (dB Min)			DCMR (dB Min)		
	1-30MHz	40MHz	50MHz	60-80MHz	30MHz	60MHz	100MHz	30MHz	60MHz	100MHz
AE-SB16005PH	-18	-14.4	-13.1	-12	-40	-35	-30	-40	-35	-30

Remark: Electrical characteristics at 25°C unless other specified

Mechanicals:



SUGGESTED PCB LAYOUT




Dimension: mm[Inch]±0.25[0.010]

Part Number: AE-SB16005PH

10/100 SMD LAN Transformer

Page: 2/2

SCHEMATICS:



Package:

